#### (19) World Intellectual Property Organization International Bureau



## 

### (43) International Publication Date 7 July 2005 (07.07.2005)

#### PCT

# (10) International Publication Number WO 2005/060631 A2

(51) International Patent Classification:

Not classified

(21) International Application Number:

PCT/US2004/041623

(22) International Filing Date:

13 December 2004 (13.12.2004)

(25) Filing Language:

English

(26) Publication Language:

**English** 

(30) Priority Data: 60/528,660

11 December 2003 (11.12.2003) US

(71) Applicant (for all designated States except US): OHIO UNIVERSITY [US/US]; 20 East Circle Drive, Suite 190, Athens, Ohio 45701-3751 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): MIRACLE, Dr. Danlel B. [US/US]; 2237 Shadowood Circle, Bellbrook, Ohio 45305 (US). TAMIRISAKANDALA, Dr. Seshacharyulu [IN/US]; 2444 Mallard Lane, Apt. #3,


Beavercreek, Ohio 45431 (US). BHAT, Dr. Radhakrishna B. [IN/US]; 2388 Edgewater Drive, Beavercreek, Ohio 45431 (US). TILEY, Dr. Jaimie S. [US/US]; 220 South State Street, Verona, Ohio 45309 (US).

- (74) Agent: FROST, Kristin J.; 800 Superior Avenue, Suite 1400, Cleveland, Ohio 44114-2688 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM.

[Continued on next page]

(54) Title: TITANIUM ALLOY MICROSTRUCTURAL REFINEMENT METHOD AND HIGH TEMPERATURE, HIGH STRAIN RATE SUPERPLASTIC FORMING OF TITANIUM ALLOYS





(57) Abstract: A method for relining the microstructure of titanium alloys in a single thermomechanical processing step, wherein the titanium alloy comprises boron. In some embodiments, the method comprises the steps of first adding boron to the titanium alloy then subjecting the boron-containing titanium alloy to a thermomechanical processing step. Also provided is a method for achieving superplasticity in titanium alloys comprising the steps of selecting a boron-containing titanium alloy, determining the temperature and strain rate necessary to achieve beta superplasticity, and applying sufficient temperature and strain rate to the boron-containing titanium alloy to deform the alloy to the desired shape. Also provided methods of forming titanium alloy parts and the parts prepared by these methods.

WO 2005/060631 A2